

CLIC WALL®

Traditional wall systems



ClicWall®



Up to 5x faster
Instant finishing



Just click and ready

UNICLIC 
PATENTED TECHNOLOGY





ClicWall: time-saving, easy-to-install click panels.

ClicWall® is UNILIN's revolutionary wall-cladding system using patented Uniclic technology, enabling you to fit your **ClicWall®** with consummate ease and up to 5 times faster than more traditional wall-cladding systems. What is more, once fitted, no further finishing is required. As such, **ClicWall®** brings a time-saving, durable and virtually seamless solution that is perfectly suited for larger wall surfaces and accent applications.

The **ClicWall®** system consists of high floor-to-ceiling panels that are 60 cm in width on an MDF base. The system is also available as boards for made-to-measure furniture applications. The low-maintenance top layer is scratch-resistant, colourfast and washable. **ClicWall®** combines unrivalled ease of installation with a contemporary aesthetic. Courtesy of the wide range of colours, designs and accessories, you can rest safe in the knowledge you'll get a perfect finish.




ClicWall® is environment-friendly, thanks to the use of PEFC-labelled wood varieties.



fast installation



click system



virtually seamless



resistant to
water splashes



UV-resistant



scratch-resistant



easy to clean



also available
in fire category B



ClicWall®Deco, the ultimate wall-cladding system to be finished as you prefer.

ClicWall®Deco gives professionals the leeway to finish wall panels entirely to choice. This wall-cladding system is based on the existing version of **ClicWall®**. However, instead of the familiar design coat, this MDF panel comes with a paint grade layer, allowing you to embellish **ClicWall®Deco** panels using paint, textile sheet, wall paper and even digital print!

All of which means **ClicWall®Deco** is quickly fitted whilst enabling you to lend your panels the finishing touch of your choice. Not to mention the fact that you are avoiding dirt and wet plastering.



ClicWall®Deco is environment-friendly, thanks to the use of PEFC-labelled wood varieties.



fast installation



click system



instant decoration





Marne Oak

H387 BST
 



Solara Oak

H339 BST
 



Amazonia Linewood

H689 W03
 




Granulo

F976 BST



Soft White Linewood

WE13 W03
 



Soft White

WE13 CST
 




Silicon

UD96 CST
 



Otter Linewood

U115 W03
 



Jasmina

UD72 CST
 



Brushed Metal

F939 CST
 

PEFC-certified
MDF core, 10 mm thick

Resistant melamine
counter layer

Resistant melamine
top layer



Colour match with HPL & MFC products available
from the Formica®Unilin Collection

Surface structures

CST = softpearl - **BST** = topmat - **W03** = structured Linewood

Clicwall, instant finishing.


- Very fast installation
- Easy installation due to patented interlocking system
- Virtually seamless design
- Wood décor or uni-colours of your choice
- "Dry" installation - no additional finishing required!



fast installation



click system



virtually seamless



resistant to
water splashes



UV-resistant



scratch-resistant



easy to clean



also available
in fire category B

Clicwall Deco, choose your own finishing.

- Very fast installation
- Easy installation due to patented interlocking system
- Totally seamless design
- Finishing as per your choice: painting, wallpapering or digital printing



Paint



Textile sheet



Wall Paper



Digital print - infinite possibilities



fast installation



click system



instant decoration



Clicwall Fire Retardant, fire-resistant walls.

- Fire retardant ClicWall
- All the advantages and identical finishing of ClicWall
- Certificate Euro Class B-S2-D0
- Meets the most stringent fire safety requirements






Technical product specifications

10 mm MDF panels, PEFC-certified, both sides finished with a strong melamine coating (Clicwall) or primer coating (Clicwall Deco). 2 long sides with Uniclic® profile, 2 head sides. Fire retardant mdf category B-S2-D0 (Clicwall FR).

Dimensions

2785 x 618 x 10 mm (gross)

2785 x 600 x 10 mm (net)



In stock

10 colours available from stock

Other colours, substrates or dimensions on request

Packaging

2 panels/pack

3,44 m² gross / 3,34 m² net

Accessories

- Flexible indoor and outdoor corner profiles with matching décor
- Aluminium outdoor corner profile with minimalist design
- Paintable skirting board: With Incizo technology, you can cut to any desired height
- Skirting board with matching décor

Separately available


Possible substructures



Metal substructure



Wooden substructure




Wooden frame



Wooden slates directly on the wall

Combined substructures are also an option.

Possible fixing systems



Screws



Staples



Glue with powerful elastic glue kit

For installation instructions and technical specifications, please refer to **www.clicwall.com**



UNILIN bvba, division panels

Ambachtenstraat 68 · 8870 Izegem · Belgium · T +32 51 30 49 32 · F +32 51 31 26 20 · info.panels@unilin.com

Check out our company and our products at www.unilinpanels.com



www.clicwall.com